




TWO-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)




ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



TWO-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



NOTES

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.



HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	1 of 2
Scale	7/64" = 1"
Date	Jan. 29, 2024

Drawing No.
TP-SALIGHT
1h




CS-S SA LIGHT

SIDE OF WALL

ASSEMBLY

FLUSH WITH ONE

TWO-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



(MULTIPLE PENETRATIONS) SALIGHT-1a.030227 ANY NON-FIRE-RATED, SMOKE- OR MIN. 1/2" BEAD SOUND-RATED **CS-S SA LIGHT AT CONCRETE WALL** POINT-OF-CONTACT **ASSEMBLY OR** ON BOTH SIDES OF **CONCRETE BLOCK** WALL ASSEMBLY WALL ASSEMBLY THROUGH **PENETRATION** MINERAL WOOL OR MIN. 1/4" DEPTH **GLASS-FIBER**

ONE-SIDED APPLICATIONS

NOTES:

• HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.

INSULATION

[OPTIONAL] SLEEVE

- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021 OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	2 of 2
Scale	7/64" = 1"
Date	Jan. 29, 2024


Drawing No. **TP-SALIGHT** 1_b




TWO-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)




ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



TWO-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



NOTES:

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON
 FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	1 of 2
Scale	7/64" = 1"
Date	Jan. 29, 2024


TP-SALIGHT 2b



TWO-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



ONE-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



NOTES:

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021 OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.



HILTI, Inc. Plano, Texas USA (800) 879-8000 Sheet 2 of 2

Scale 7/64" = 1"


Date Jan. 29, 2024

TP-SALIGHT 2b




TP-SALIGHT-1a.03022


TWO-SIDED (PHASED) APPLICATIONS (INDIVIDUAL PENETRATIONS)




ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



NOTES:

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	1 of 2
Scale	7/64" = 1"
Date	lan 20 2024


TP-SALIGHT
3a




ONE-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



ONE-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



ONE-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



THIS SECTION WAS INTENTIONALLY LEFT BLANK.

NOTES

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	2 of 2
Scale	7/64" = 1"
Date	Jan. 29, 2024


TP-SALIGHT
3a




TOP-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)




BOTTOM-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)



TOP-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)



BOTTOM-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)



NOTES

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON
 FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.



HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	1 of 2
Scale	7/64" = 1"
Date	Jan. 29, 2024


Drawing No.

TP-SALIGHT

4a



TOP-SIDE APPLICATIONS (MULTIPLE PENETRATIONS)



BOTTOM-SIDE APPLICATIONS (MULTIPLE PENETRATIONS) TP-SALIGHT-1a.030221 THROUGH PENETRATION MINERAL WOOL OR **GLASS-FIBER** INSULATION ANY NON-FIRE-RATED, SMOKE- OR SOUND-RATED CONCRETE **FLOOR ASSEMBLY** MIN. 1/4" DEPTH MIN. 1/2" BEAD **CS-S SA LIGHT CS-S SA LIGHT AT FLUSH WITH** POINT-OF-CONTACT **BOTTOM SIDE OF** ON BOTTOM SIDE FLOOR ASSEMBLY OF FLOOR **ASSEMBLY**

NOTES:

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021 OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet 2 of 2 Scale 7/64" = 1" Date Jan. 29, 2024


Drawing No. TP-SALIGHT




TWO-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)




TOP-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)



BOTTOM-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)



TWO-SIDED APPLICATIONS (INDIVIDUAL PENETRATIONS)



- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	1 of 3
Scale	7/64" = 1"
Date	Jan. 29, 2024


Drawing No. TP-SALIGHT 5a




TOP-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)




BOTTOM-SIDE APPLICATIONS (INDIVIDUAL PENETRATIONS)



TWO-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



TWO-SIDED APPLICATIONS (MULTIPLE PENETRATIONS)



- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
- FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021, OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.




HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet	2 of 3
Scale	7/64" = 1"
Date	Jan. 29, 2024

Drawing No. TP-SALIGHT 5a



BOTTOM-SIDE APPLICATIONS (MULTIPLE PENETRATIONS)



THIS SECTION WAS INTENTIONALLY LEFT BLANK.

NOTES:

- HILTI CS-S SA LIGHT SMOKE AND ACOUSTIC LIGHTWEIGHT SEALANT MAY BE INSTALLED WHERE IT IS NECESSARY TO RESTRICT SMOKE MIGRATION THROUGH NON FIRE-RATED ASSEMBLIES.
- NOT FOR FIRE-RATED ASSEMBLIES.
- LUBRIZOL CPVC COMPATIBLE (FBC™ SYSTEM COMPATIBLE).
- FOR BITUMINOUS COATED CAST IRON PIPE COMPATIBILITY REACH OUT TO HILTI TECHNICAL SUPPORT FOR DETAILS.
- REFER TO PRODUCT LITERATURE FOR COMPLETE DETAILS ON INSTALLATION, SUITABLE APPLICATIONS, AND LIMITATIONS.
 FOR APPLICATIONS THAT DO NOT MEET THE CONDITIONS ABOVE, CONTACT HILTI TECHNICAL SUPPORT.
- THESE DETAILS REPRESENT GENERAL INSTALLATION GUIDELINES TO SATISFY SMOKE PARTITION SEALING REQUIREMENTS OF THE INTERNATIONAL BUILDING CODE (2009, 2012, 2015, 2018, 2021 OR 2024). OBTAIN AUTHORITY HAVING JURISDICTION APPROVAL PRIOR TO INSTALLATION.



HILTI, Inc. Plano, Texas USA (800) 879-8000

Sheet 3 of 3 Scale 7/64" = 1" Date Jan. 29, 2024

Drawing No. TP-SALIGHT 5a