

TLSX.R13203 Roof Deck Fasteners

Page Bottom

Roof Deck Fasteners

See General Information for Roof Deck Fasteners

HILTI INC 5400 S 122ND EAST AVE TULSA, OK 74146 USA

Fasteners and powder actuated fasteners identified as "X-ENP-19 L15", "X-ENP-19 L15MX", "X-ENP-19 L15MXR", "X-EDN19 THQ12M", "X-EDNK22 THQ12M", "X-HSN 24" and "S-MD 12-24x1-5/8 M HWH5" or "S-MD05Z 5.5 x 40" for use in Construction Nos. <u>58</u>, <u>87</u>, <u>156</u> and <u>157</u>.

Note: These fasteners may also be used in all Roof Deck Assemblies Classified for uplift purposes, where the structural supports are a minimum of 1/8- inch thick when using "X-EDNK22 THQ12M", "X-HSN 24" and "S-MD 12-24x1-5/8 M HWH5 or S-MD05Z 5.5 x 40" fasteners, or a minimum of 3/16-inch thick when using "X-EDN19 THQ12M" fasteners, or a minimum of 1/4-inch thick when using "X-ENP-19 L15MX", "X-ENP-19 L15MX", "X-ENP-19 L15MXR fasteners; and the deck units are A, B or F, or any other similar types having a minimum thickness of 22 MSG.

Also refer to Design Information Section supplements to Fire Resistance Ratings - ANSI/UL263 Section III Floor-Ceilings and Roof-Ceilings, paragraphs 23 and 24.

Last Updated on 2013-06-13

 Questions?
 Print this page
 Terms of Use
 Page Top

 Constraint
 Constraint
 Constraint
 Constraint

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the <u>UL Environment database</u> for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".

R13203