

25

VARIES

VARIES

10

100

304137

SPECIAL

SPECIAL

AS REQ'D 304889

AS REQ'D 382897

INSTALLATION INFO.

INSTALLATION.

VERIFY FIELD CONDITIONS PRIOR TO ORDERING &

ADEQUACY OF CABLE TRAY MAX. SPAN NOT CONSIDERED BY

EA WING NUT MQM-F1/2"-F

EA 1/2" WASHER (HDG)

13 AS REQ'D EA MI HEX NUT M12-F-SL-WS 3/4"

EA 1/2"x1" HEX HEAD BOLT (HDG)

EA ONEHAND SCREW MIA-OH90

9

10

6

6

12 AS REQ'D



All loading and design criteria supplied by customer is assumed accurate. Only the stated Design Assumptions were considered, and must be verified by the responsible Engineer of Record (EOR). The basis of Hilti component and connection design is the published data in the current Hilti Technical Guide, including material and cross-section properties, allowable load values, factors of safety, methods of calculation, and limiting factors. The EOR must verify suitability for any specific application, and the capacity of the supportive structure to receive the shown configuration and associated reaction loads. Modification to components and/or design may alter performance and must be evaluated by the EOR

TYPICAL DETAIL TYPE:

## CABLE TRAY SUPPORT

TYPICAL DETAIL DESCRIPTION:

## **GOALPOST - MULTI TRAY**

DESIGNED BY:	REVIEWED BY:
KL	AJV
DRAWN BY:	ISSUE DATE:
GAB	31 DEC 14

1	NO:	DESCRIPTION:	DATE:
	<u>A</u>	ORIGINAL ISSUE	31 DEC 14
_	_		
-	_		
-	_		
-	_		
-	_		
-	_		
-	_		
-	_		
-	_		
-			
-			
_	_		
-	_		
-	_		
-	_		
-	_		

TYPICAL DETAIL NOMENCLATURE:

## CT-GP06-C

DRAWING NUMBER:	SHEET:
01	1/1