The accurate, one touch solution.

PD 5 Laser Range Meter

The new Hilti PD 5 Laser Range Meter is the only tool of its kind that concentrates solely on the fundamental task of measuring distances. A person working alone with this tool can accurately measure distances of up to 230 feet at the touch of a button. The PD 5 is even easier to use than a smart phone, helping reduce errors. Just aim at the target, press the button and read the distance from the display. The PD 5 takes the harshest jobsite conditions in stride. Thanks to the well-protected rugged rubberized casing, it is water and dust resistant.



PULSE III POWER



FLEET MANAGEMENT

*Some limitations apply. Contact Hilti for details

Accuracy± 1/20 in (± 1.5 mm)Measuring range8 in - 230 ft (.2 - 70 m)FunctionsSingle and continuous measurementLaser class635 nm, class 2 (IEC 825-1), class II (FDA 21 CFR)Protection classIP 55Battery life with alkaline battery8,000 measurements (2 AAA Alkaline batteries)Operating temperature+14° F to +122° F (-10° C to 50° C)Dimensions (L x W x H)6.5 x 1.3 x .8 in (164 x 33 x 21 mm)	Technical Data	PD 5
Functions Single and continuous measurement Laser class 635 nm, class 2 (IEC 825-1), class II (FDA 21 CFR) Protection class IP 55 Battery life with alkaline battery 8,000 measurements (2 AAA Alkaline batteries) Operating temperature +14° F to +122° F (-10° C to 50° C)	Accuracy	± 1/20 in (± 1.5 mm)
Laser class 635 nm, class 2 (IEC 825-1), class II (FDA 21 CFR) Protection class IP 55 Battery life with alkaline battery 8,000 measurements (2 AAA Alkaline batteries) Operating temperature +14° F to +122° F (-10° C to 50° C)	Measuring range	8 in - 230 ft (.2 - 70 m)
Protection class IP 55 Battery life with alkaline battery 8,000 measurements (2 AAA Alkaline batteries) Operating temperature +14° F to +122° F (-10° C to 50° C)	Functions	Single and continuous measurement
Battery life with alkaline battery8,000 measurements (2 AAA Alkaline batteries)Operating temperature+14° F to +122° F (-10° C to 50° C)	Laser class	635 nm, class 2 (IEC 825-1),class II (FDA 21 CFR)
Operating temperature +14° F to +122° F (-10° C to 50° C)	Protection class	IP 55
	Battery life with alkaline battery	8,000 measurements (2 AAA Alkaline batteries)
Dimensions (L x W x H) 6.5 x 1.3 x .8 in (164 x 33 x 21 mm)	Operating temperature	+14° F to +122° F (-10° C to 50° C)
	Dimensions (L x W x H)	6.5 x 1.3 x .8 in (164 x 33 x 21 mm)
Weight 0.22 lb (100 grams)	Weight	0.22 lb (100 grams)

Order Information

Description	Package Contents	Item No.
PD 5 Laser Range Meter	Includes tool, PDA 605 toolbag, PDA 615 belt clip, (2) "AAA" batteries and operating instructions	02004789

Applications

- Measuring distances from 8" to 230' quickly and accurately
- Measuring heights where alternative measuring methods fail
- Measuring quickly and safely in places where access is difficult

Outperform

- Simple and intuitive to use
- Single-button operation
- New compact design that fits in every pocket

Outlast

- Water and dust resistant
- Rugged and durable





Hilti. Outperform. Outlast.

